



Gulf DEXRON® VI ATF

Supreme performance Automatic Transmission Fluid

Product Description

Gulf DEXRON® VI ATF is a supreme performance long life automatic transmission fluid specially developed for all 2006 and beyond General Motors vehicles equipped with Hydramatic automatic transmissions. This fluid is formulated with exceptional quality base fluids and advanced additive technology to provide outstanding oxidation resistance, friction durability, wear protection and shear stability. It is designed to provide twice the service life of a DEXRON® III (H) ATF and offers exceptional anti-shudder & smooth shift performance. It is approved as service fill fluid against General Motors DEXRON® VI (license number: J 60304 & J-60311) specification. It is fully back serviceable for DEXRON® III (H), DEXRON® III, DEXRON® II E and DEXRON® II D applications and offers enhanced performance for both new and older transmissions.

Features & Benefits

- Outstanding thermo-oxidative stability, friction durability, wear protection and shear stability lead to
 - Longer fluid life
 - Longer transmission life
 - Enhanced performance in both new and older transmissions
- Optimised frictional properties prevent clutch shudder and enable smooth gear shifting & extended clutch durability
- Exceptional viscosity profile, improved torque transfer and low viscosity of this oil help in improving fuel economy
- Enhanced foam control maintains responsive shifts and reduces wear on bearings, bushings and gears
- Excellent low temperature fluidity leads to easy pumping in the hydraulic circuits
- Special rust and corrosion inhibitors protect critical parts against rust and corrosion throughout the service life
- Excellent seal compatibility ensures longer seal life and reduces possibility of oil leakage

Applications

- Recommended for & meets the warranty requirements of all 2006 and beyond General Motors vehicles with six speed Hydra-Matic transmissions requiring DEXRON® VI quality fluids.
- Being fully back serviceable, it is also recommended for automatic transmissions requiring DEXRON® III (H), DEXRON® III, DEXRON® II E and DEXRON® II D quality oils for enhanced performance

Specifications, Approvals & Typical Properties

Has the following Approvals		
General Motors DEXRON® VI (license number: J-60304 & J-60311)		
Typical Properties		
Test Parameters	ASTM Method	Typical Values
Viscosity @ 100 °C, cSt	D 445	6.0
Viscosity Index	D 2270	153
Flash Point, °C	D 92	200
Pour Point, °C	D 97	-51
Brookfield Viscosity @ -40 °C, cP	D 2983	11500
Density @ 15°C, Kg/l	D 1298	0.841

DEXRON® is a registered trademark of General Motors Corporation

September, 2006

Properties mentioned above are typical only and minor variations, which do not affect the product performances, are to be expected in normal manufacturing. The above information is based on past history of the grade only and must not be construed as a guarantee of performance. Follow equipment manufacturer's recommendations for performance level and viscosity grade. The Material Safety Data Sheet for this product is available from your nearest Gulf Distributor.

Gulf Oil International

The information contained herein is believed to be correct at time of publication. No warranty expressed or implied is given concerning the accuracy of the information or the suitability of the products. Gulf Oil International reserves the right to modify and change its products and specifications without prior notice.

www.gulfoilltd.com