



## Gulf Synthetic Gear Oil

### *Synthetic heavy-duty industrial gear oil*

#### Product Description

**Gulf Synthetic Gear Oil** series are synthetic heavy duty industrial gear oils offering outstanding lubrication performance and load carrying capacity under severe operating conditions including shock loading. These are formulated from water soluble Polyalkylene Glycol (PAG) base stocks which are known for providing excellent micropitting resistance, thermal properties, excellent low temperature fluidity, EP properties and oxidation resistance,. The combination of extremely high viscosity index base stocks coupled with high performance additive technology provides excellent thermal stability, protection against scuffing and resistance against micropitting under wide operating temperature range.

#### Features & Benefits

- Outstanding load carrying capability and micro-pitting resistance protects gears against scuffing and wear leading to enhanced equipment life and reduced maintenance costs
- Superior thermo-oxidative stability provides enhanced system cleanliness and enables longer service intervals
- Excellent resistance to rust and corrosion protection ensures trouble free operation
- Good seal and paint compatibility with a wide variety of seals and paints

#### Applications

- ISO VG 150 – 680 meets the Siemens (Flender) T 7300 A+B specification for Flender Helical, Bevel, Worm and Planetary gear units.
- ISO VG 320 is specifically developed for lubrication of wind turbine gear box manufactured by Hansen, Flender, Rexroth, FAG, etc where such quality lubricants are recommended
- Heavy-duty industrial enclosed gear boxes operating under severe conditions like high load, extreme temperatures and wide temperature ranges.
- Fill for life systems, chain and conveyors, kiln and ovens, textile lubricants, compressor (Reciprocating, Rotary screw)
- Bearing and circulation systems where high temperatures are encountered

#### Materials Compatibility

- Compatible with common seal and gasket materials
- For high temperature applications, Nitrile Rubber (NBR), Fluoro-Silicone or Vinyl-Metyl Polysiloxane (Q) are recommended
- Ordinary industrial paints soften in presence these products, internal gearboxes surfaces should be unpainted or coated with resistant materials.

#### Specifications & Typical Properties

ISO Viscosity Grade		150	220	320	460	680
<b>Meet the following Specifications</b>						
DIN 51517 Part 3		X	X	X	X	X
David Brown Type G Lubricant		X	X	X	X	
Siemens (Flender) T 7300 A+B		X	X	X	X	X
<b>Typical Properties</b>						
<b>Test Parameters</b>	<b>ASTM</b>	<b>Test Values</b>				
Viscosity @ 40 °C, cSt	D 445	152	224	312	475	727
Viscosity Index	D 2270	201	240	247	259	272
Flash Point, °C	D 92	282	282	284	282	285
Pour Point, °C	D 97	-47	-42	-39	-36	-33
Density @ 15°C, Kg/l	D 1298	1.057	1.057	1.058	1.067	1.072
FZG, fail load stage	DIN 51324	>12	>12	>12	>12	>12

July 2016

**Note: These products should not be mixed with mineral oil or PAO based products.**

Properties mentioned above are typical only and minor variations, which do not affect the product performances, are to be expected in normal manufacturing. The above information is based on past history of the grade only and must not be construed as a guarantee of performance. Follow equipment manufacturer's recommendations for performance level and viscosity grade. The Material Safety Data Sheet for this product is available from your nearest Gulf Distributor.

**Gulf Oil International**

The information contained herein is believed to be correct at time of publication. No warranty expressed or implied is given concerning the accuracy of the information or the suitability of the products. Gulf Oil International reserves the right to modify and change its products and specifications without prior notice.

[www.gulfoilltd.com](http://www.gulfoilltd.com)